

## HAZARD CLASS LABELS

Required for shipping hazmat by ground, rail, air and sea, hazard class labels must be used on certain bulk and non-bulk packages.

- Heavyweight, coated paper or chemical- and weather-resistant vinyl
- Durable, permanent adhesive
- 4" x 4"
- Vinyl labels pass IMO 90-day seawater immersion test
- Paper and vinyl labels pass the DOT 30-day exposure requirement
- Meets 49 CFR 172.400; ICAO 5-3; and IMO 5.2 design requirements



### 1 HAZARD CLASS—Explosives

 <b>EXPLOSIVE 1.1A</b> 1 Compatibility Group A, B, C, D, E, F, G, J or L LEXPI11A to LEXPI11L SLEXP11A to SLEXP11L LEXPI11AS to LEXPI11LS SLEXP11AS to SLEXP11LS	 <b>EXPLOSIVE 1.2B</b> 1 Compatibility Group B, C, D, E, F, G, H, J, K or L LEXPI2B to LEXPI2L SLEXP2B to SLEXP2L LEXPI2BS to LEXPI2LS SLEXP2BS to SLEXP2LS	 <b>EXPLOSIVE 1.3C</b> 1 Compatibility Group C, F, G, H, J, K or L LEXPI3C to LEXPI3L SLEXP3C to SLEXP3L LEXPI3CS to LEXPI3LS SLEXP3CS to SLEXP3LS	 <b>1.4 EXPLOSIVE B</b> 1 Compatibility Group B, C, D, E, F, G or S LEXP14B to LEXP14S SLEXP14B to SLEXP14S LEXP14BS to LEXP14SS SLEXP14BS to SLEXP14SS
 <b>1.5 BLASTING AGENT D</b> 1 Compatibility Group D LEXP15D SLEXP15D LEXP15DS SLEXP15DS		 <b>1.6 EXPLOSIVE N</b> 1 Compatibility Group N LEXP16N SLEXP16N LEXP16NS SLEXP16NS	 1 LEXP-SUB SLEXP-SUBR

### 4 HAZARD CLASS—Flammable Solids

 <b>FLAMMABLE SOLID</b> 4 HML5 HMSL5 HML5C HML5S HMSL5S	 <b>SPONTANEOUSLY COMBUSTIBLE</b> 4 HML21 HMSL21 HML21S HMSL21S	 <b>DAINGEROUS WHEN WET</b> 4 HML23 HMSL23 HML23S HMSL23S
--	---	---

### 5 HAZARD CLASS—Oxidizer & Organic Peroxide

 <b>OXIDIZER</b> 5.1 HML11 HMSL11 HML11C HML11S HMSL11S	 <b>ORGANIC PEROXIDE</b> 5.2 HML52 HMSL52 HML52S HMSL52S
--	--

### 7 HAZARD CLASS—Radioactive

 <b>RADIOACTIVE I</b> 7 HML14 HMSL14 HML14S HMSL14S	 <b>FISSILE</b> 7 HML33 HMSL33 HML33S HMSL33S	 <b>RADIOACTIVE II</b> 7 HML15 HMSL15 HML15S HMSL15S	 <b>RADIOACTIVE III</b> 7 HML16 HMSL16 HML16S HMSL16S
---	---	--	---