

# NEWTEX Technical Data Sheet

Phone: (585) 924-9135 or (800) 836-1001 | Technical Dept: tech@newtex.com | Website: www.newtex.com



## Z-Flex X20 Gloves [Leather Palm]

Aluminized Gloves made from Z-Flex® Aluminized Fabric to protect from high radiant temperatures, sparks, and molten metal splash.

### General Information

Item ID	2100002
Style	X20
Finish/Coating	Z-Flex Aluminized
Minimum Order Requirement	12 pairs

### Construction

Fiber Type	Texturized Fiberglass
------------	-----------------------

### Physical Properties

	US	Metric
Length	14.00 in	35.56 cm
Size	One Size Fits All	One Size Fits All

### Thermal Properties

	US	Metric
Peak Temp	600 °F	315 °C
Operating Temp	500 °F	260 °C
Radiant Heat Resistance	3000 °F	1650 °C

### Testing & Certifications

#### Z-Flex | 300 Series has been tested to the following standards:

- EN 407: Tested for Resistance to Contact Heat, Convective Heat, Radiant Heat, and Flammability
- EN 388: Tested for Abrasion Resistance and Tear Resistance

### Other Information

- The aluminized surface is not recommended for direct contact with temperatures above 350°F (175°C).

For additional technical information, please contact tech@newtex.com

