

Universal Pillows #GPIL1818 - 18" x 18", 10 pillows/package



Use SpillTech® Universal Pillows to absorb high-volume leaks and spills of oils, coolants, solvents or water.

GPIL1818 Specifications

| | |
|-----------------------------|---------------------------|
| Dimensions: | 18" W x 18" L |
| Shipping Dimensions: | 24" W x 16" L x 11.5" H |
| Sold as: | 10 pillows per package |
| Color: | Gray |
| Composition: | Poly Blend |
| Absorbency: | Up to 23 gal. per package |
| Absorbency per: | Up to 2.3 gal. per pillow |
| Weight: | 11.5 lbs. |
| # per Pallet: | 35 |
| Incinerable: | Yes |
| Ship Class: | 175 |

Metric Equivalent Specifications

| | |
|-----------------------------|------------------------------|
| Dimensions: | 45.7cm W x 45.7cm L |
| Shipping Dimensions: | 61cm W x 40.6cm L x 29.2cm H |
| Dimensions: | |
| Absorbency: | Up to 87.1 L per package |
| Absorbency per: | Up to 8.7 L per pillow |
| Weight: | 5.2 kg |

GPIL1818 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com