


APPROX WEIGHT: 663.42 lbs.  
DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!!

# LIFT MASTER BOOM, ORBIT TELESCOPING BOOM - LM-OBT-8-24

\*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\*  
ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON



## \*--MAXIMUM SINGLE HOOK CAPACITIES

DISTANCE	36"	48"	60"	72"	84"	96"	108"	120"	132"	144"
CAPACITY	8000	6650	6000	5300	4650	4000	3500	3000	2600	2200

## STANDARD FEATURES

- MODEL NUMBER IS LM-OBT-8-24
- CAPACITY IS 8,000 LBS
- LOST LOAD - 675 LBS
- MAXIMUM TILT ANGLE IS 37°
- OVERALL HEIGHT - 28 7/8"
- HEIGHT (MAX TILTED) - 96 1/8"
- LENGTH RETRACTED - 85 1/4"
- LENGTH EXTENDED - 148 1/2"
- OVERALL WIDTH IS 32"
- 36" MINIMUM HOOK POINT
- 144" MAXIMUM HOOK POINT
- HOOK HEIGHT - 5 1/8"
- HOOK HEIGHT (MAX TILTED) - 76 9/16"
- USABLE FORK POCKET - 7 1/4" x 2 1/4"
- 24" FORK POCKET CENTERS
- EFFECTIVE THICKNESS: LESS THAN 1"

## SPECIAL FEATURES

NONE

NEVER EXCEED LOAD CENTER RATING PER FORK TRUCK MANUFACTURER'S GUIDELINES.  
DO NOT USE THIS FORK TRUCK ATTACHEMENT IF LOAD WILL EXCEED FORK TRUCK MANUFACTURER'S LOAD CENTER RATING.

DIMENSION TOLERANCE ± 1/4"

APPROVAL	I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.	
	<b>ANY MODIFIED UNITS ARE NON-RETURNABLE</b>	
	[ ] As drawn [ ] As marked	
	Signed: _____ Date: _____	
Printed Name: _____		
LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING		

FOR INTERNAL USE ONLY PROJECT SIGN OFF	
SALES	
ENG.	
FAB.	
POWER	

DISTRIBUTOR'S NAME:		P.O.#
VESTIL MANUFACTURING		X
W.O.#		X
DRAWN BY:	B.NOETHNAGEL	DATE: 7/6/2015
REFERENCE:	X	SCALE: 1:18
QUOTED LEAD TIME:	X	QUOTE # X
FILE NAME:		08-007-131