

“Closure Instructions” Bentley World Packaging, LTD. Heavy Weight - 4D Wood Box

UN 4D / Y193 / S / **
USA / +AA7182

IMPORTANT WARNING!

This packing instruction details the correct assembly of the 4D packaging design. Deviation may result in non-compliance and voiding of the certification. Bentley World Packaging, LTD. is not responsible for any packaging using substitute components incorrectly. If further information is ever needed, please contact Bentley World Packaging, LTD. at Ph# 1-410-483-6250, or send an email to: info@bentleywp.com

BOX USE

The user of this “UN” Certified Plywood box must follow these instructions carefully. Any solid product or material / article may be used in this packaging.

Items and materials using Packing Groups II or III may be used in this box.

This plywood box is designed to be used in an upright position. (Runners on the Bottom)

Cushioning / Closure Requirements

No Cushioning is required for materials that fit snugly into the box. However, blocking and/or bracing (using compatible materials) are required for loose items.

Items inside must not move within the packaging once the box is closed.

This box comes complete with a lid / top for closure. Cleats / 2x4 side up.

We have pre-drilled twenty (20) pilot holes for the lid / top. Three-inch (3”) screws are provided in a plastic bag. They must be drilled into the lid / top of the box.

Note: Screws must be tightened to become flush with the top of the box (“ALL THE WAY IN”). Lid must become flush / tight with the top and the sides and ends.

Glue is **not required or recommended** for the lid.

Gross Weight

The combined gross weight of product and box must not exceed 193 Kgs / 425 Lbs scale / gross weight.

The approximate weight of product inside the box must not exceed 156 Kgs / 343 Lbs net weight.

The UN Specification mark on the side of the box reflects the maximum weight when shipped.