

## HazMat Fleet Spill Kit #SPKHZ-FLEET - Absorbs up to 10.7 Gallons



Be prepared for fast response with a SpillTech® HazMat Spill Kit!



**SpillTech**

Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)

## SPKHZ-FLEET Specifications

## Metric Equivalent Specifications

<b>Dimensions:</b>	22" W x 20" L x 9" H
<b>Shipping Dimensions:</b>	20" W x 22" L x 9" H
<b>Sold as:</b>	1 per package
<b>Absorbency:</b>	Up to 10.7 gal. per package
<b>Weight:</b>	9.57 lbs.
<b># per Pallet:</b>	32
<b>Incinerable:</b>	No
<b>Ship Class:</b>	92.5
<b>Includes:</b>	50 - 10" x 14" Yellow HazMat HeavyWeight FineFiber Pads (YPF1014H) 2 - 3" x 4' Yellow HazMat Sorbent Socks (YSO430) 1 - 1 lb. Plug & Dike Epoxy Putty (A-PND) 9 - Assorted Wooden Plugs (A-WOODPLUGS-LG) 2 - 18" X 30" Yellow Disposal Bags & Ties (A-DISP BAG-SM) 2 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 8" x 17" x 20" Yellow Nylon "Spill Responder" Zippered Tote Bag (A-YTOTE)

<b>Dimensions:</b>	55.9cm W x 50.8cm L x 22.9cm H
<b>Shipping Dimensions:</b>	50.8cm W x 55.9cm L x 22.9cm H
<b>Absorbency:</b>	Up to 40.5 L per package
<b>Weight:</b>	4.3 kg

## SPKHZ-FLEET Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

### Technical Documents:

(Available at [spilltech.com](http://spilltech.com))

Product Data Sheet (PDS)



**SpillTech**

Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)